

10/17/00



Jc954 U.S. PTO

10/18/00

A

IBM Docket No. FR9-1999-0079 US1

 Jc813 U.S. PTO
 09/690207
 10/17/00

In the United States Patent and Trademark Office

Patent Application Transmittal

Transmitted herewith for filing is the Patent Application of:

Inventors(s): Jean Francois Le Pennec, Guy Euget

For: Method and System for Establishing a Virtual Path Capability in a Frame Relay Network

Enclosed are

- 25 pages of specification, including 20 claims, plus 4 sheets of drawings.
- X An assignment of the invention to International Business Machines Corporation, Armonk, New York 10504.
- X A certified copy of a/an **European** application.
- X Declaration and Power of Attorney.
PTO-1449 & references
- X A return post card
- Other:

Filing Fee Calculation (For Other Than Small Entity)

Basic Fee:						\$710.00
Claims Fees:	Filed	Limit	Extra		Rate per Extra	
Total claims:	20	20	0		\$18.00	\$0.00
Independent claims:	2	3	0		\$80.00	\$0.00
Multiple Dependent Claim Presented					\$270.00	\$0.00
Total:						\$710.00

Please charge Deposit Account **09-0464** for the **Total** set forth above. The Commissioner is authorized to charge payment of any additional filing fees required under 37 CFR §1.16 and any patent application processing fees under 37 CFR §1.17 or to credit any overpayment to the identified account. A duplicate copy of this sheet is enclosed.

Express Mail Certificate

Express Mail Label No: EK956406077US

Date: Oct. 17, 2000

I hereby certify that I am depositing the papers identified above with the U.S. Postal Service "Express Mail Post Office to Address" service on the above date, addressed to the Assistant Commissioner for Patents, Washington, DC 20231

Saundra S. Christopher

Saundra S. Christopher

BY: *Daniel E. McConnell*

Daniel E. McConnell

Attorney of Record Reg. No. 20,360

Date: Oct. 17, 2000

IBM Corporation 2Y7/B656
Intellectual Property Law
PO Box 12195
Res. Tri. Park, NC 27709

Telephone: 919-543- 1105 FAX 919-543-3634

METHOD AND SYSTEM FOR ESTABLISHING A VIRTUAL PATH CAPABILITY IN A FRAME RELAY NETWORK

5

BACKGROUND OF THE INVENTION

1. Technical Field:

The present invention relates in general to packet switching network communications and, in particular, to frame relay networks. Still more particularly, the present invention relates to methods for establishing a virtual path capability in a frame relay network.

2. Description of the Related Art:

Frame relay networks provide high speed virtual private network (VPN) capable of point-to-point high speed data transmission. Frame relay systems delimit and align frames on a channel using flags identifying the beginning and ending of a frame. Frame relay systems typically support virtual circuit multiplexing and demultiplexing through the use of a Data Link Connection Identifier (DLCI) in the frame. A DLCI identifies a virtual connection on a channel at a user to network or network to network interface. Consequently, A DLCI specifies a data link layer entity to which information is delivered or received from. A DLCI is specified in a particular field in each frame in the data link layer. The DLCI field may be either unstructured or structured.

Figure 1 shows a diagram of a particular network for illustrating concepts of prior art as well as the present invention. A source user 10 sends a message over a prior art system to a destination user at address 64.2.3.4. A router 10 which receives the traffic to this destination, references an internal routing table, determines that this address is mapped with DLCI 27. Router 12 then puts the contents of the message in a frame and sets the DCLI field to DLCI 27 before sending this frame over the Frame Relay network. The frame is received by a first switching node which then consults its internal routing table to determine that the frame is to be mapped to DLCI 992. After performing the mapping, first switching node 16 relays the frame to a second switching node 18 which maps the frame to DLCI 35 and then sends the frame to router 20 which forwards the frame to the destination user at address 64.2.3.4.

As described above, DLCIs are pre-mapped to a particular destination. A routing table within each switching node specifies the proper output port for each DLCI frame. A unique DLCI is required to establish each of a plurality of virtual circuits which utilize a single switching node even though each of the plurality of virtual circuits connect to a single switching node over a common trunk. The DLCI field in each frame typically has only 10 bits and most of the possible bit combinations are reserved or used to convey specific user

information. As a result there is a limited supply of
unique DLCIs available. Furthermore, connectionless
operations could be established within a network if the
requirement is met that each frame arrives at the correct
port designated by the destination identifier.

5

SUMMARY OF THE INVENTION

5 All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

10 An the object of the present invention is to achieve a method which enables a plurality of virtual circuits which utilize a single trunk between two switching nodes of a Frame Relay network to use a single common Data Link Connection Identifier (DLCI). Another object of the invention is to achieve a protocol enabling several virtual circuits using the same trunk between two switching nodes of a frame relay network to be aggregated in a single virtual path.

20 A method is disclosed for establishing a Virtual Path (VP) capacity in a Frame Relay network whereby frames are transmitted over a select plurality of virtual circuits from a first switching node to a second switching node. A first switching node transmits to a second switching node a control message with a Data Link Connection Identifier (DLCI) having a predetermined value. This control message defines a virtual path aggregate in which two or more virtual circuits from among a plurality of virtual circuits are combined and identifies the individual virtual circuits which are combined to form the virtual path.

30 According to one aspect of the invention, the control message includes a particular field (VCID) containing one byte for identifying each virtual circuit

which is combined to form the virtual path. The control message also includes: a field for specifying a source Virtual Circuit Identifier (SVCID) which corresponds to the input network adapter used by the virtual circuit in the first switching node; a field for a Source Port Identifier (SPID), which corresponds to the input port used by the virtual circuit in the first switching node; a Destination Virtual Circuit Identifier (DVCID) field corresponding to the output adapter used by the virtual circuit in the second switching node; and a Destination Port Identifier (DPID) field corresponding to the output port used by the virtual circuit in the second switching node.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts an illustrative embodiment of a Frame Relay network in which the methods and systems of the present invention may advantageously be utilized;

Figure 2 depicts a block-diagram of a Frame Relay network having several virtual circuits established between a first switching node and a second switching node which are combined using the methods of the present invention to form a virtual path aggregate;

Figure 3 is a diagram for illustrating a handshake protocol exchanged between the two switching nodes of **Figure 2** for establishing a virtual path aggregate which utilizes the methods of the invention;

Figure 4 is the format of a control message utilized by an embodiment of the present invention, which is sent from a first switching node to a second switching node;

Figure 5 shows a format of a data frame, utilized by an embodiment of the present invention, in which a virtual path between the two switching nodes is established; and

5

Figures 6A and 6B represent, respectively, a source table and a destination table of an switching node which are updated by a control message according to the methods of the invention.

FIG. 5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures and in particular with reference to **Figure 1**, there is a virtual connection established between switching node **16** and switching node **18** using a Data Link Connection Identifier (DLCI) 992. In this embodiment, several virtual circuits are established through switching node **16** and switching **18** (or between two other switching nodes of Frame Relay network **14**).

Referring now to **Figure 2** which illustrates an embodiment of the present invention. Switching node **16** is linked to external network elements through virtual circuits **VC2**, **VC4** on a link L0 and **VC1**, **VC3** and **VC5** on another link L1. Switching node **18** is connected to virtual circuit **VC1** on link L2, virtual circuit **VC5** on link L3 and virtual circuits **VC2**, **VC3** on link L4. The inputting switching node **16** to virtual circuit **VC5** connects with another switching node **24**. External links may be network ports but may be also trunks connected to other nodes of network **14**.

Switching node **16** connects to a backbone node switching node **26**, which connects to another backbone switching node **18**. Switching node **18** connects to switching node **28**. A virtual path **12** is established according to the methods of the invention, which is a combination of common portions of virtual circuits **VC1**, **VC2**, **VC3** that reside between switching nodes **16** and **18**. In this embodiment, virtual circuit **VC5** which corresponds

to a class of service different from the class of service of virtual circuits **VC1**, **VC2**, and **VC3**, is not included in virtual path **12** to illustrate the coexistence of standard virtual circuits with virtual paths according to the invention. In this embodiment, the virtual path **12**, which is implemented between two switching nodes **16** and **18** includes intermediary switching nodes **26** and **28**. However, a virtual path **12** of the present invention may be implemented between two adjacent nodes as well.

The assignment of virtual circuits to a new virtual path is configured within both switching nodes **16** and **18**, while the intermediary switching nodes remain transparent. An embodiment of a protocol is defined, in accordance with the methods of the present invention, to support the data exchange and the negotiation between the two nodes for configuring the nodes to comprehend the new virtual path aggregate. This embodiment is illustrated in **Figure 3**.

A control message is sent from switching node **16** to switching node **18** to request the configuration of a new virtual path. To indicate the purpose of this message, the DLCI field is set to predefined value 999, which is one of the values which are reserved for layer management of the frame bearer service. Node **18**, receives this control message, determines from the DLCI value of 999 that the purpose of the message is to establish a virtual path, and then records the chain of VCs assigned to this new virtual path aggregate identified by the DLCIn.

Node **18** answers the request from node **16** by sending a control message either acknowledging affirmatively or rejecting the request to establish a virtual path. Affirmative acknowledgment is sent if the virtual circuits are operational and the quality of service requested in the line with the authorized parameters. A rejection is sent if the VCs are not operational in an aggregation mode. In the preferred embodiment, status information is included in the rejection message for identifying the reason for the rejection, which is forwarded to the network management system for filing and analysis. If no answer from node **18** is received by node **16** then node **18** may not have understand the request. A timer is used within node **16** to detect this error, which may also be forwarded to the network management system for filing and analysis.

If a rejection message or no answer is received by switching node **16**, then the virtual path is not formed and error information is forwarded to the network management system for filing and analysis.

If an acknowledge message is received by node **16** from node **18** and no other condition occurred which prevents forming the virtual, then node **16** responds by sending node **18** a message affirming the virtual path aggregate. Otherwise, depending on the message received by node **16**, a message is sent by node **16** to node **18** either indicating the error or acknowledging the rejection from node **18**. Node **18** may also use a timer to detect the absence of a response from node **16** and then

generate an error condition communicating the absence of a response to system management.

Figure 4 illustrates an embodiment, which is in accordance with the present invention, of a format for a control message sent from a first switching node to second switching node to initiate the configuration of a virtual path. This control message has a defined data structure and uses a specific value for DLCI (in this case DLCI set to 999) which is predefined, through network or inter-node protocol, to indicate a negotiation for configuring a virtual path between the two nodes. A specific DLCI may be assigned for each logical connection between two nodes of the network where a virtual path aggregate is needed. In the disclosed embodiment, each field of the control message, shown in **Figure 4**, is defined as follows in table 1.

Table 1

FIELD NAME	BITS WITHIN FIELD	FIELD DEFINITION
VPID		The Trunk Virtual Path Identifier
AGGT		Aggregation type 14 bits (0-13)
	0,1	Defines nb of bytes used for merging VC filed in data frame (1, 2 or 3 bytes) corresponds to the size of the VCID2,3 : number of bytes for Source Port definition (6,14, 22 or 30 bits)
	4,5	Number of bytes for Destination Port definition (6,14, 22 or 30 bits)
	6,7	Defines the size of the QoS Field : 0, 1, 2 or 3 bytes (Flow ID + QoS)
	8 to 12	Indicates whether the message is a single command or multiple commands and if multiple, then the number of VCs included
	13	Spare bit
VCID		Trunk VC identifier

This control message, may be used to set up one virtual path aggregate and one or more VCs, which have portions that are combined to form a new virtual path. Preferably, whenever one or more new VCs are established between the two nodes, a control message is sent to include the new VC(s) in the virtual path. For this reason, a control message need never contain many VC identifications.

In each control message, of the disclosed embodiment, the field after DLCI 999 of 10 bits contains the Virtual Path Identifier (VPID) which identifies the common DLCI N for transmitting the frames belonging to all aggregated VCs between the two nodes.

The AGGT field of 14 bits specifies the aggregation type and mode corresponding to the aggregated VCs listed after this field. The AGGT field allows alignment of the boundary of the VCs definition to an exact number of bytes.

The Virtual Circuit Identification, specified in the VCID field, contains as many bytes as there are VCs to be combined. For each VC, the fields, which follow the VCID field, define the Source Virtual Circuit Identifier (corresponding to the input adapter of switching node **16**), the Source Port Identifier (corresponding to the input port switching node **16**), the Destination Virtual Circuit Identifier (corresponding to the output adapter of switching node **18**), the Destination

Port Identifier (corresponding to the output port of switching node **18**) and the QoS field which defines Priority, Queue, Traffic type, Flow ID (per VC).

5 **Figure 5** shows an embodiment of a structure for a data frame according to the methods of the present invention. The header is the VP identification which fits into the DLCI field. The VC identification of the VC number i , that is $VCID(i)$ is put the first byte of the data field which is ended by the Frame Check Sequence (FCS) field. The control message, sent to request configuration of a virtual path, as shown in reference to **Figure 4**, informs the receiving switching node which port and on which VC this data frame is to be mapped.

10 Each time a control message is sent between the two switching nodes, each node updates its internal identification table, such as those shown in **Figures 6A** and **6B**. For the sending node, the source table maps, for each coupled VP/VC respectively identified by VPID and VCID, to the Source VC identifier and the Source Port Identifier. Similarly, for the receiving node, the destination table maps for each coupled VP/VC, to the Destination VC identifier and Destination Port identifier.

15 Each time a frame is received on an input adapter in switching node **16**, the node's internal source table is consulted to determine whether this frame is to be encapsulated into a VP structure of the present invention or transmitted as a normal VC frame. Similarly, the receive adapter of switching node **18**, consults an

internal table to determine whether this frame is a normal VC frame which will be mapped using the classical forwarding mechanism or is a VP encapsulated frame of the present invention which will be forwarded to the port specified by the defined VC given by the line pointed by this frame's VP/VC identifier.

Note that any virtual circuit which is no longer used should be deleted from a virtual path. For this purpose a supplementary field in the control message, such as the VCID field, is reserved in the disclosed embodiment. Alternatively, the first switching node may utilize a time counter for detecting extended periods of non-activity by each VC which triggers the first switching node to remove the inactive VC from the VP. In this case, The source table is overwritten in the first switching node. An internode protocol message from the first switching node to the second switching node is sent to remove the inactive VC from the destination table.

The preferred embodiment enables some VCs or the entire VP to be canceled by a particular predefined control message in which bit 13 of the AGGT field (See table 1) is set to 1. In this case, if all the VCID fields following the AGGT field have all their bits set to 0, this indicates that the entire VP is to be removed. Only some VCID fields may have all their bits set to 0 to indicate that only these VCs are to be removed from the VP. This method provides for an efficient re-configuration.

While the invention has been particularly shown
and described with reference to a preferred embodiment,
it will be understood by those skilled in the art that
various changes in form and detail may be made therein
without departing from the spirit and scope of the
invention.

CLAIMS

What is claimed is:

5 1. A method for establishing a virtual path within a
6 frame relay network wherein frames are transmitted over a
7 plurality of virtual circuits from a first switching node
8 to a second switching node, said methods comprising:

9 transmitting by said first switching node to said
10 second switching node, a first control message requesting
11 a virtual path be established, and specifying two or more
12 virtual circuits to be combined to form said virtual
13 path;
14

15 receiving a frame, at said second switching node,
16 wherein said frame has an identifier corresponding to
17 said virtual path; and
18

19 forwarding said frame, utilizing said second
20 switching node, to a destination determined based on said
21 two or more said virtual circuits specified in said first
22 control message.

1 2. The methods of claim 1, wherein said step of
2 transmitting said first control message includes the step
3 Of handling a data link connection identifier,
4 corresponding to a predetermined value, for identifying
5 said purpose of first control message.

1 3. The method of claim 1, wherein said step of
2 transmitting said first control message includes the step
3 Of transmitting a field for identifying each of said two
4 or more said virtual circuits.

1 4. The method of claim 1, wherein said step of
2 transmitting said first control message includes the step
3 of transmitting information specifying said virtual path,
4 wherein said information is comprised of:

5 a source virtual circuit identifier, which
6 corresponds to an input adapter of said first switching
7 node;

8 a source port identifier, which corresponds to an
9 input port of said first switching node;

10 a destination virtual circuit identifier, which
11 corresponds to an output adapter of said second switching
12 node; and

13 a destination port identifier, which corresponds to
14 an output port of said second switching node.

1 5. The method of claim 1, further comprising the step
2 of:

3 transmitting by said second switching node to said
4 first switching node, a second control message conveying
5 acknowledgment of said request to establish said virtual

6 path or rejection of said request to establish said
7 virtual path.

1 6. The method of claim 5, further comprising the step
2 of:

3 transmitting to said first switching node to said
4 second switching node, a third control message
5 acknowledging a reception of said second control message
6 by said first switching node.

7 7. The method of claim 1, further comprising the step
8 of:

9 starting a timeout timer, by said first switching
10 node, when said first control message is transmitted;

11 detecting an error when said timeout timer expires
prior to receiving a second control message from said
second switching node, wherein said second control
message conveys acknowledgment of said request to
establish said virtual path or rejection of said request
to establish said virtual path.

1 8. The method of claim 1, further comprising the step
2 of:

3 transmitting to said second switching node, a forth
4 control message, sent by said first switching network,

5 for removing one of said two or more virtual circuits
6 from said virtual path.

1 9. The method of claim 1, further comprising the step
2 of:

3 transmitting to said second switching, a fifth
4 control message, sent by said first switching network,
5 for canceling said virtual path.

6 10. The method of claim 8, further comprising the step
7 of:

8 starting a plurality of activities timers, wherein
9 each of said two or more virtual circuits combined to
10 form said virtual path corresponds to one of said
activities timers;

11 resetting, for each frame received for said two or
12 more virtual circuits combined to form said virtual path,
13 the corresponding said activity-timer;

14 detecting, by the expiration of one of said
activity-timers, an extended period of non-activity by
one of said virtual circuits which correspond to said
expired activity-timer; and

transmitting to said second switching node, a forth control message, sent by said first switching network, for removing from said virtual path, said virtual circuit corresponding to said expired activity-timer.

11. A system for establishing a virtual path within a frame relay, said system comprising:

a frame relay network including a plurality of virtual circuits for transmitting frames from a first switching node to a second switching node;

a virtual path established by a first control message transmitted by said first switching node to said second switching node, defining a virtual path, and specifying two or more virtual circuits to be combined to form said virtual path;

a frame, having an identifier corresponding to said defined virtual path, received by said second switching node and then forward said frame to a destination determined by said two or more virtual circuits specified in said control message.

12. The system of claim 11, wherein said control message includes a data link connection identifier, corresponding to a predetermined value, for identifying said purpose of first control message.

1 13. The system of claim 11, wherein said control message
2 includes a field for identifying each of said two or more
3 virtual circuits.

1 14. The system of claim 11, wherein said first control
2 message includes information specifying said virtual
3 path, wherein said information is comprised of:

4 a source virtual circuit identifier, which
5 corresponds to the input adapter of said first switching
6 node;

7 a source port identifier, which corresponds to the
8 input port of said first switching node;

9 a destination virtual circuit identifier, which
10 corresponds to the output adapter of said second
11 switching node; and

12 a destination port identifier, which corresponds to
13 the output port of said second switching node.

1 15. The system of claim 11, further comprising:

2 a second control message transmitted by said second
3 switching node to said first switching node, conveying
4 acknowledgment of said request to establish said virtual
5 path or rejection of said request to establish said
6 virtual path.

1 16. The system of claim 15, wherein said first switching
2 node is adapted to transmit in response to said second
3 control message, to said second switching node a third
4 control message acknowledging a reception of said second
5 control message by said first switching node.

1 17. The system of claim 11, further comprising:

2
3 a timeout timer, set by said first switching node
4 when said first control message is transmitted;

5
6 detecting an error when said timeout timer expires
7 prior to receiving a second control message from said
8 second switching node, wherein said second control
9 message conveys acknowledgment of said request to
10 establish said virtual path or rejection of said request
11 to establish said virtual path.

12 18. The system of claim 11, further comprising:

13 a forth control message transmitted by said first
14 switching node to said second switching node, for
15 removing one of said two or more virtual circuits from
16 said virtual path.

1 19. The method of claim 11, wherein said first switching
2 node is adapted to transmit to said second switching, a
3 fifth control message, for canceling said virtual path.

1 20. The system of claim 18, further comprising:

2
3 a plurality of activities timers, wherein one said
4 activities timers corresponds to each of said two or more
5 virtual circuits combined to form said virtual path,
6 wherein for each frame received for said two or more
7 virtual circuits combined to form said virtual path, said
8 corresponding said activity-timer is reset;

9 an error condition signal, wherein said error
10 condition signal is generated from the detection by the
11 expiration of one of said activity-timers, an extended
12 period of non-activity by one of said virtual circuits
13 which correspond to said expired activity-timer; and

14 a forth control message, sent by said first
15 switching network in response to said error condition
16 signal, for removing from said virtual path, said virtual
17 circuit corresponding to said expired activity-timer.
18

ABSTRACT OF THE DISCLOSURE**METHOD AND SYSTEM FOR ESTABLISHING A VIRTUAL PATH
CAPABILITY IN A FRAME RELAY NETWORK**

5

A method and system for establishing a Virtual Path (VP12) capability in a Frame Relay network wherein frames are transmitted over a plurality of virtual circuits from a first switching node to a second switching node. A control message is transmitter from the first switching node to the second switching node with a Data Link Connection Identifier (DLCI) having a predetermined value indicating the purpose of the control message which is to define a virtual path aggregating at least two virtual circuits selected from multiple virtual circuits. The control message contains the identification of the virtual circuits aggregated in the defined virtual path.

10

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100





FIG. 1






FIG. 3




FIG. 4




FIG. 5

SOURCE TABLE

VPID	VCID	SVCID	SPID

FIG. 6A

DESTINATION TABLE

VPID	VCID	DVCID	DPID

FIG. 6B

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**Method and System for Establishing a Virtual Path Capability in a
Frame Relay Network**

the specification of which is identified by the attorney (IBM) Docket Number appearing above.

I hereby state that I have reviewed and understand the contents of the above- identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

<u>Number</u>	<u>Country</u>	<u>Day/Month/Year</u>	<u>Priority Claimed</u>
99480112.4	Europe	21/10/99	Yes

I hereby claim the benefit (a) under Title 35, United States Code, §119(e) of any U.S. application listed below and identified as a provisional application or (b) under Title 35, United States Code, §120 of any U.S. application listed below and not identified as a provisional application, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior U.S. application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Prior U.S. Applications

<u>Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
-------------------	--------------------	---------------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Daniel E. McConnell, Reg. No. 20,360; Joscelyn G. Cockburn, Reg. No. 27,069; Horace St. Julian, Reg. No. 30,329; and Christopher A. Hughes, Reg. No. 26,914.

Send all correspondence to: Daniel E. McConnell, IBM Corporation 2Y7/B656; PO Box 12195; Research Triangle Park, NC 27709.

First Inventor: Jean Francois Le Pennec

Signature:

Jean Francois Le Pennec *October 11, 2000*

Date

Residence: 11 Chemin de la Serena
Route de Gairaut
06100 Nice - France

Citizenship: French

Post Office Address: Same as above

Second Inventor: Guy Euget

Signature:

Guy EUGET *Sept 22, 2000*

Date

Residence: 592 Chemin de la Sine
06140 Vence - France

Citizenship: French

Post Office Address: Same as above